

# TRAXTER<sup>®</sup>

SOLID SKID STEER TYRES



**Puncture-Proof**

No Downtime & Repair Costs

**Long-Life**

4-5 Times of Pneumatic Tyres

**Cost-Effective**

Low Operating Costs & Overheads

**Safe & Stable Ride**

No Blowouts, Improved Balance

**Comfort**

Softer Ride for Lowered Fatigue

**Sound Investment**

Reduced Cost per Hour

**Built Solid**

## TECHNICAL SPECIFICATIONS

Size	Rim	Pattern		Overall Diameter		Section Width		Tread Depth		Load Capacity		Replaces Pneumatic Tyre
				mm	inch	mm	inch	mm	32nd	6 mph lbs	10 km/h kg	
18x7-10	5.00	SSK-03	1R	448	17.6	175	6.9	40	52	2200	1000	18x8.50-8
23x7-10	5.00	SSK-01	1R	583	22.9	178	7.1	50	64	3740	1700	5.70-12, 23x8.5-12
5.70-12	4.00	SSK-03	1R	570	22.8	145	5.7	40	52	2860	1300	5.70-12
26x9-16	6.00	SSK-03	1R	650	25.6	220	8.7	50	64	4070	1850	26x12-12, 27x8.50-15, 27x10-15
30x9-16	6.00	SSK-02	2R	750	29.5	205	8.1	60	76	4400	2000	10-16.5
30x9-16	6.00	SSK-03	1R	750	29.5	215	8.5	60	76	4400	2000	10-16.5
30x9-16	6.00	SSK-SM	-	755	29.7	220	8.7	70	88	6160	2800	10-16.5
30x10-16	6.00	SSK-01	1R	767	30.2	222	8.7	65	83	7590	3450	10-16.5
30x10-16	6.00	SSK-03	1R	767	30.2	240	9.4	66	83	5500	2500	10-16.5
30x10-16	6.00	SSK-03	2R	745	29.3	235	9.3	52	66	5500	2500	10-16.5
30x10-16	6.00	SSK-04	1R	767	30.2	240	9.5	65	83	5500	2500	10-16.5
30x10-16	6.00	SSK-05	1R	767	30.2	251	9.9	64	82	5940	2700	10-16.5
30x10-16	6.00	SSK-06	1R	767	30.2	251	9.9	66	83	5940	2700	10-16.5
30x10-18	7.00	SSK-02	2R	770	30.3	245	9.6	52	66	4840	2200	10-16.5
30x12-16	8.00	SSK-01	2R	767	30.2	290	11.4	65	83	6160	2800	31.5x13-16.5
33x9-16	6.00	SSK-02	2R	850	33.5	230	9.1	74	93	9570	4350	12-16.5
33x9-16	6.00	SSK-03	1R	850	33.5	235	9.3	83	105	9570	4350	12-16.5
33x9-16	6.00	SSK-SM	-	850	33.5	230	9.1	80	101	11250	5110	12-16.5
33x12-16	8.00	SSK-05	1R	835	32.9	298	11.7	73	92	11440	5200	12-16.5
33x12-18	7.00	SSK-04	1R	830	32.7	287	11.3	75	96	11440	5200	12-16.5
33x12-18	7.00	SSK-05	1R	835	32.9	298	11.7	73	92	12100	5500	12-16.5
33x12-18	7.00	SSK-06	1R	830	32.7	287	11.3	75	96	12100	5500	12-16.5
33x11-20	7.50	SSK-SM	-	865	34.1	275	10.9	58	73	12350	5600	12-16.5
33x12-20	7.50	SSK-01	1R	850	33.5	273	10.5	62	78	10340	4700	12-16.5
33x12-20	7.50	SSK-02	1R/2R	850	33.5	273	10.5	62	78	10340	4700	12-16.5
33x12-20	7.50	SSK-03	1R	840	33.1	266	10.5	62	78	10340	4700	12-16.5
33x14-20	8.50	SSK-04	1R	850	33.5	340	10.5	62	78	10670	4850	33x15.5-16.5
36x13-20	7.50	SSK-02	1R	915	36.0	305	12.0	75	95	12320	5600	14-17.5
40x14-24	8.50	SSK-02	1R	975	38.4	355	14.0	80	101	13200	6000	15-19.5

1R = 1 Row Aperture , 2R = 2 Row Aperture



**SSK-01**



**SSK-02**



**SSK-03**



**SSK-SM**



**SSK-04\*\***



**SSK-05**



**SSK-06**

Supplied as Ready to Fit assemblies

Sidewall apertures for softer ride

Fitted on heavy duty, reusable wheels

Suitable for use on dry, wet & hard surfaces

\*\*Patented Pattern (D813793)

**RECOMMENDED FOR SEVERE APPLICATIONS**

Construction  
Solid-Waste Management

Scrap & Recycling Yards  
Steel Mills, Smelters and Furnaces

Mining & Quarrying  
Industrial Plants



[www.tridentlatam.com](http://www.tridentlatam.com)

[ventas@tridentlatam.com](mailto:ventas@tridentlatam.com)